

# SAFETY DATA SHEET



Date Issued : 3/26/2014  
MSDS No : EDSP200

## GRAIN NEUTRAL SPIRITS 200

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** GRAIN NEUTRAL SPIRITS 200

**MANUFACTURER**

Distributed by Tarr, LLC  
P.O. Box 12570  
Portland, OR 97212  
**Service Number:** 1-800-442-5069

**24 HR. EMERGENCY TELEPHONE NUMBERS**

**CANUTEC (Canadian Transportation) :**(613) 996 - 6666  
**CHEMTREC (US Transportation) :**(800) 424 - 9300

### 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS**

**Health:**

Flammable Liquids, Category 1B

**GHS LABEL**



Flame

**SIGNAL WORD:** WARNING

**HAZARD STATEMENTS**

H226: Flammable liquid and vapour.

**PRECAUTIONARY STATEMENT(S)**

**Prevention:**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

**EMERGENCY OVERVIEW**

**IMMEDIATE CONCERNS:** WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful. May cause central nervous system depression. May be irritating to eyes and skin.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness, swelling and eye damage.

**GRAIN NEUTRAL SPIRITS 200**

**SKIN:** Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**INGESTION:** Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (headache, drowsiness, dizziness, loss of coordination and fatigue).

**INHALATION:** May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

**MEDICAL CONDITIONS AGGRAVATED:** Preexisting diseases in or history of ailments involving skin, central nervous system, liver and kidney.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt. %	CAS
Ethanol	100	64-17-5

**4. FIRST AID MEASURES**

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

**SKIN:** Wash with soap and water for at least 15 minutes. Get medical attention, if irritation develops or persists.

**INGESTION:** DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

**ACUTE TOXICITY:** Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, and nausea.

**5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use "alcohol resistant" foam, dry chemical, or CO<sub>2</sub>. Water may be ineffective, but water applied as a spray can absorb some of the fire's heat and should be used to keep fire-exposed containers cool.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.

**EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

**FIRE FIGHTING PROCEDURES:** WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

**6. ACCIDENTAL RELEASE MEASURES**

**GENERAL PROCEDURES:** WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially

**GRAIN NEUTRAL SPIRITS 200**

trained or qualified personnel should handle the emergency.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**COMMENTS:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Ethanol	TWA	1000	1900	1000	1884	400	980
	STEL					400	1,225

**ENGINEERING CONTROLS:** Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

**SKIN:** Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

**PROTECTIVE CLOTHING:** Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

**WORK HYGIENIC PRACTICES:** Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**COMMENTS:** May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**GRAIN NEUTRAL SPIRITS 200**

**PHYSICAL STATE:** Liquid

**ODOR:** Alcohol odor.

**COLOR:** Clear, colorless liquid.

**pH:** NA = Not Applicable

**PERCENT VOLATILE:** 100

**FLASHPOINT AND METHOD:** (55°F) TAG CC

**FLAMMABLE LIMITS:** 0.033 to 0.19

**AUTOIGNITION TEMPERATURE:** (685°F)

**VAPOR PRESSURE:** 44.6

**VAPOR DENSITY:** Heavier than air.

**BOILING POINT:** (173°F)

**FREEZING POINT:** NDA = no data available.

**MELTING POINT:** (-173°F)

**SOLUBILITY IN WATER:** Soluble

**EVAPORATION RATE:** Slower than ether.

**DENSITY:** 6.62

**SPECIFIC GRAVITY:** 0.78 to 0.80

**10. STABILITY AND REACTIVITY**

**STABLE:** Yes

**POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

**INCOMPATIBLE MATERIALS:** This product is incompatible with strong acids or bases, oxidizers, alkali metals, and halogens.

**11. TOXICOLOGICAL INFORMATION**

**TARGET ORGANS:** This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain.

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The preferred options for disposal are to send to licensed reclaimers, or to permitted

**GRAIN NEUTRAL SPIRITS 200**

incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

**EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN!** Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

**RCRA/EPA WASTE INFORMATION:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Ethanol

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** UN 1170

**PACKING GROUP:** II

**NAERG:** 127

**LABEL:** Flammable liquid

**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Flammable  
Liquid

S28: After contact with skin, wash immediately with plenty of water and soap.

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

**313 REPORTABLE INGREDIENTS:** To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.

**302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** Listed.

**GRAIN NEUTRAL SPIRITS 200****CANADA****WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Flammable  
Liquid


**GENERAL COMMENTS:** The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

**16. OTHER INFORMATION**

**PREPARED BY:** COMPLIANCE

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>	<input checked="" type="checkbox"/>	

**NFPA CODES**

**NFPA STORAGE CLASSIFICATION:** These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

**HMIS RATINGS NOTES:** The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the SDS must be considered. Personal protection rating to be supplied by user depending on use conditions.

**MANUFACTURER DISCLAIMER:** The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.